# $\mathsf{DECK}^{\scriptscriptstyle\mathsf{IM}}$

# CB1972 and CB1975

### Single Layer Diffuser - Surface Mount



Visalighting.com/products/Deck

Type: Project: Location: Location:





### DIMENSIONS<sup>1</sup>

Depth is measured from wall to front of fixture

W = Width H = Height D = Depth


	CB1972	CB1975	
W	23-1/2" (597 mm)	34-1/2" (876 mm	W
Н	1-1/2" (	38 mm)	HC
D	2-1/2" (	(64 mm)	JBC Option
	Diffuser	JBC Option	Side View  Diffuser Retainer  Diffuser Housing  Diffuser Option

#### **FEATURES**


- Remote driver
- Horizontal or vertical mounting
- Surface mount
- Diffuser is 1/8" thick clear acrylic with matte finish
- No VOC powder coat paint finish; low VOC clear coat on metal finishes
- ETL listed for damp locations

#### **RELATIVE SCALE DRAWING**

800-788-VISA



#### **PHOTOMETRICS**











Page 1

VisaLighting.com

### **DECK** (cont.) CB1972 and CB1975 Single Layer Diffuser - Surface Mount



#### Fill in shaded boxes using information listed below **MVOLT** MODEL<sup>1</sup> SOURCE<sup>2</sup> **VOLTAGE** OPTION(S)3 **DIFFUSER RETAINER HOUSING FINISH** CB1972 • L30K(H) MVOLT **FINISH** DCC See last page for CB1975 • L30K(L) JBC See last page for finish order codes • MRI L35K(H) See page 1 finish order codes L35K(L) XPS • L40K(H) • L40K(L)

#### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

		CB197	72	CB1975			
Source	ССТ	Delivered Lumens Power (Watts)		Delivered Lumens	Power (Watts)		
• L30K(H)	3000K	950	14	1400	21		
• L30K(L)	3000K	650	10	950	13		
L35K(H)	3500K	950	14	1400	21		
L35K(L)	3500K	650	650 10		13		
• L40K(H)	4000K 950		14	1400	21		
• L40K(L)	4000K	650 10		950	13		

#### **VOLTAGE**


<b>MVOLT</b> 120-277V, 50/60 Hz
---------------------------------

### OPTIONS<sup>3</sup> (Multiple Selections Allowed)

#### ▲ Option availability may be interdependent with Other Options

DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)
JBC	Junction box cover (5" square) for use with an existing 4" junction box. Painted to match surface housing finish
• MRI	MRI room application, not available with dimming
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with <b>XPS</b>

### MOUNTING DETAIL



## **DECK** (cont.) CB1972 and CB1975 Single Layer Diffuser - Surface Mount



### DECK PRODUCT FAMILY

	Cuufa sa Maumt	24"	• CB1972
Single Layer	Surface Mount	35"	• CB1975
Diffuser	Deceased Mount	24"	• CB1971
	Recessed Mount	35"	• CB1974
	Cunfo co Mount	24"	• CB1978
Dual Layer	Surface Mount	35"	• CB1980
Diffuser	Decessed Mount	24"	• CB1977
	Recessed Mount	35"	• CB1979

See <u>Visalighting.com/products/Deck</u> for more information

#### SUGGESTED VARIATIONS

- 2700K
- Custom colors
- Nominal 4' height

### **DECK** (cont.) CB1972 and CB1975 Single Layer Diffuser - Surface Mount



#### **FINISHES**

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard) Powder coat finishes available for Diffuser Retainer or Housing

AGGY	Agate Grey	ALGN	Alpine Green	BJBG	Baja Beige	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue
DEOR	Deoro Gold	GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey
SBGN	Sagebrush	SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red
	Green		State diey		S.S. a laupe		Canyon		Wille		. c cr black		

#### Alternative Metal Finishes (Premium) Metal finishes available for Diffuser Retainer



#### Metal Finish (Premium)



**BA** Brushed Aluminum