DECK™

CB1977 and CB1979

Dual Layer Diffuser - Recessed Mount



Visalighting.com/products/Deck

Type: _____ Project: _____ Location: _____





DIMENSIONS¹


Depth is measured from wall to front of fixture

W = Width H = Height D = Depth RW = Recessed Width RH = Recessed Height RD = Recessed Depth


	CB1977	CB1979							
W	23-1/2" (597 mm)	34-1/2" (876 mm)							
Н	3-1/2" (89 mm)								
D	1-1/4" (32 mm)								
RW	23-3/4" (603 mm)	34-3/4" (883 mm)							
RH	1-7/8" (48 mm)							
RD	3-1/4" (83 mm)								

FEATURES


- Integral high power factor electronic driver
- Horizontal or vertical mounting
- Semi-recessed (mud required; mud frame included)
- Recessed backbox is available for pre-shipment for rough-in installation
- Dual Layer diffuser; rear layer is 1/8" thick frosted acrylic with matte finish
- No VOC powder coat paint finish; low VOC clear coat on metal finishes
- ETL listed for damp locations



RELATIVE SCALE DRAWING



PHOTOMETRICS











DECK (cont.) CB1977 and CB1979 **Dual Layer Diffuser - Recessed Mount**



Fill in shaded boxes using information listed below MVOLT OPTION(S)4 MODEL1 SOURCE² **VOLTAGE DIFFUSER RETAINER HOUSING FINISH** DIFFUSER3 CB1977 • L30K(H) MVOLT **FINISH** AMDCC See last page for • KA CB1979 • L30K(L) RB finish order codes See last page for • OLIN TTF L35K(H) See page 1 finish order codes L35K(L) • SL XPS • L40K(H) • L40K(L)

SOURCE² (Select one)


Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

		CB197	17	CB1979		
Source	ССТ	Delivered Lumens Power (Watts)		Delivered Lumens	Power (Watts)	
• L30K(H)	3000K	950	14	1400	21	
• L30K(L)	3000K	650	10	950	13	
L35K(H)	3500K	950	14	1400	21	
L35K(L)	3500K	650	10	950	13	
• L40K(H)	4000K	950	14	1400	21	
• L40K(L)	4000K	650	10	950	13	

120-277V, 50/60 Hz

VOLTAGE


MVOLT



DIFFUSER³ (Select one)


Rear diffuser is Matte White Acrylic

AM	Clear acrylic with matte finish							
• KA	Kauri Lumicor®							
• OLIN Oyster Linen Lumicor								
• SL	Silver Spun Lumicor							





MOUNTING DETAIL



OPTIONS⁴ (Multiple Selections Allowed)

Option availability may be interdependent with 0ther 0ptions

DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)
RB	Pre-ship recessed backbox
TTF	Tile Trim Flange; Painted - specify Finish Code (see finishes)
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS

DECK (cont.) CB1977 and CB1979 Dual Layer Diffuser - Recessed Mount



DECK PRODUCT FAMILY

	Cuufa sa Maumt	24"	• CB1972
Single Layer	Surface Mount	35"	• CB1975
Diffuser	Deceased Mount	24"	• CB1971
	Recessed Mount	35"	• CB1974
	Cunfo co Mount	24"	• CB1978
Dual Layer	Surface Mount	35"	• CB1980
Diffuser	Decessed Mount	24"	• CB1977
	Recessed Mount	35"	• CB1979

See <u>Visalighting.com/products/Deck</u> for more information

SUGGESTED VARIATIONS

- 2700K
- Custom colors
- Nominal 4' height

DECK (cont.) CB1977 and CB1979 Dual Layer Diffuser - Recessed Mount



FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard) Powder coat finishes available for Diffuser Retainer or Housing

AGGY	Agate Grey	ALGN	Alpine Green	BJBG	Baja Beige	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue
DEOR	Deoro Gold	GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey
SBGN	Sagebrush Green	SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red

Alternative Metal Finishes (Premium) Metal finishes available for Diffuser Retainer



Metal Finish (Premium)



BA Brushed Aluminum