## CB5301 AIR FOIL™

### 51" Indoor Wall Sconce with downlight option



VisaLighting.com/products/Air-Foil

Type: Project: Location:








#### **DIMENSIONS**


Depth is measured from wall to front of fixture

W = Width H = Height D = Depth

W 7-1/4" (184 mm) H 51" (1295 mm) D 18-1/2" (470 mm)









#### **FEATURES**

- · Integral driver
- Modular design for replacement of source and driver
- Optional recessed downlight with high and low lumen input
- Edge lit trim
- Color changing RGB is DMX compatible (controls by others)
- Four field adjustable aiming angles
- Matte white acrylic diffuser
- Optional specialty diffuser materials available, including Vara Kamin's Impressions of Light® images which are replicated from Kamin's original works of art
- No VOC powder coat paint finish; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not recommended for exterior applications

#### **RELATIVE SCALE DRAWING**



#### PHOTOMETRICS







## CB5301 AIR FOIL (cont.)

### 51" Indoor Wall Sconce with downlight option



#### Fill in shaded boxes using information listed below CB5301 **MVOLT** OPTION5 MODEL **BODYLIGHT**<sup>1</sup> **DOWNLIGHT<sup>2</sup> VOLTAGE** DOWNLIGHT<sup>3</sup> **FINISH** DIFFUSER OPTION 4 L30K (OPTIONAL) MVOLT **OPTICS VKMD** DCC See last page (OPTIONAL) VKMM L35K L30K(H) for finish L40K L30K(L) MED VKPG order codes L35K(H) NRW VKSS RGB L35K(L) WIDE L40K(H) Required L40K(L) with downlight option

#### BODYLIGHT<sup>1</sup> (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

Source	ССТ	Delivered Lumens	Power (Watts)
L30K	3000K	5900	49
L35K	3500K		49
L40K	4000K	6100	49
RGB			77

#### DOWNLIGHT<sup>2</sup> (Optional)

Fixture bottom is solid if no downlight is specified


Source	ССТ	Delivered Lumens	Power (Watts)
L30K(H)	3000K	2900	28
L30K(L)	3000K	1400	14
L35K(H)	3500K	3000	28
L35K(L)	3500K	1500	14
L40K(H)	4000K	3100	28
L40K(L)	4000K	1500	14

#### DOWNLIGHT OPTICS<sup>3</sup> (Optional)

Required with downlight option

MED	49° Beam
NRW	35° Beam
WIDE	70° Beam

#### FIELD ADJUSTABLE AIMING ANGLES (PLAN VIEW)



## DIFFUSER OPTION4

**VOLTAGE** 

MVOLT

Diffuser is matte white acrylic if no option is selected

120-277V, 50/60 Hz

VKMD	Vara Kamin's Moon Drops <sup>©</sup>	
VKMM	Vara Kamin's Morning Melody®	
VKPG	Vara Kamin's Priscilla's Garden®	
VKSS	Vara Kamin's Summer of Sundays®	

Vara Kamin options have been colorcorrected to 4000K CCT and are available only with L40K source









#### **EDGE LIT TRIM**



#### OPTION<sup>5</sup>

A Option availability may be interdependent with Other Options



# CB5301 AIR FOIL (cont.) 51" Indoor Wall Sconce with downlight option



#### AIR FOIL PRODUCT FAMILY

Indoor Wall	51" with downlight option	• CB5301
Sconce	55"	• CB5303
Pendant	48" H x 16" W	• CP5301
	48" H x 24" W	• CP5311
	48" H x 36" W	• CP5321
	24" H x 16" W	• CP5393
	36" H x 16" W	• CP5395
Outdoor Wall Sconce	55"	• 0W5303

See <u>VisaLighting.com/products/Air-Foil</u> for more information

#### SUGGESTED VARIATIONS

- Tandem units
- Custom printed overlay on lenses
- Graphics (school/company logos)

## CB5301 AIR FOIL (cont.) 51" Indoor Wall Sconce with downlight option



#### **FINISHES**

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)



#### Alternative Metal Finishes (Premium)



#### Metal Finish (Premium)



**BA** Brushed Aluminum