# **OLYMPIA**<sup>™</sup>

# CP4151, CP4155 and CP4159 Stem Suspension



Visalighting.com/products/Olympia

Type:	Proiect:	Location:	
.,,,.	Tojeca —	Locationi	





#### DIMENSIONS<sup>1,5</sup>

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(36) indicates an overall fixture height of 36"

#### ▲ OAH must be specified

W = Width OAH = Standard Overall Height X = Body Height NBS= Nominal Bowl Size

	CP4151	CP4155	CP4159
W	26" (660 mm)	33-7/8" (860 mm)	40-5/8" (1032 mm)
OAH	25" (635 mm)	32" (813 mm)	38" (965 mm)
Χ	7" (178 mm)	9"(229 mm)	10-1/2" (267 mm)
NBS	23x5" (584x127 mm)	31x7" (787x178 mm)	37x9" (787x229 mm)




Structural Blocking Required (CP4159) (See Detail on Page 2)


#### **FEATURES**

- Integral driver
- Modular design for replacement of LED source and driver
- Easy toolless bowl cleaning
- Mounts to standard electrical junction box (by others) with provided hardware for ceiling slopes up to 45 degrees from horizontal (CP4151 and (P4155)
- Mounts through 4" octogonal by 2-1/8" deep electrical junction box(by others) to structural blocking (by others) with provided hardware for ceiling slopes up to 45 degrees from horizontal (CP4159 only)
- Spun metal trim
- Thermally formed 1/8" thick white acrylic diffuser with matte finish
  - UV stable
    - UL-94 HB Flame Class rated
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suited for exterior applications

## **RELATIVE SCALE DRAWING**



## **PHOTOMETRICS**









# **OLYMPIA** (cont.) CP4151, CP4155 and CP4159 Stem Suspension



#### Fill in shaded boxes using information listed below **MVOLT** MODEL1 SOURCE<sup>2</sup> OPTION(S)4 **VOLTAGE FINISH DIFFUSER OPTION3** OAH<sup>5</sup> CP4151 • L30K MVOLT • ABA $\mathsf{AF}$ See last page DCC See page 1 CP4155 L35K for finish CP4159 L40K XPS order codes See page 1

### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 10%, Minimum 80CRI, within 3-step MacAdam

		CP4151			CP4155			CP4159					
	Uplight		Downlight		Uplight		Downlight		Uplight		Downlight		
SOURCE	ССТ	Delivered Lumens	Power (Watts)										
• L30K	3000K	8300		2400		12600		4100		21900		6200	
L35K	3500K	8700	78	2500	39	13100	119	4300	53	22800	205	6500	67
• L40K	4000K	8900		2600		13500		4400		23500		6700	

# DIFFUSER OPTION<sup>3</sup>

Diffuser is matte white acrylic unless ABA option is selected

• ABA Hand Painted Alabaster Alternative



#### ABA

# OPTIONS<sup>4</sup> (Multiple selections allowed)

## ▲ Option availability may be interdependent with Other Options

AF	Add Finial. Addition of AF option increases H dimension (height) by 1-1/8"			
DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)			
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS			

### **VOLTAGE**

MVOLT	120-277V, 50/60 Hz
-------	--------------------

# AF OPTION



### STRUCTURAL BLOCKING DETAIL (CP4159)



# **OLYMPIA** (cont.) CP4151, CP4155 and CP4159 Stem Suspension



# **OLYMPIA PRODUCT FAMILY**

	18" Deep Bowl	• CB3462
Sconces	20" Shallow Bowl	• CB3464
Surface Mount	18" Deep Bowl	• CM1101
Ceiling Units	26" Shallow Bowl	• CM1103
	26" Bowl	• CP4151
Stem Suspension Pendants	34" Bowl	• CP4155
rendents	41" Bowl	• CP4159
	26" Bowl	• CP4191
Cable Suspension Pendants	34" Bowl	• CP4195
. c.i.ddiito	41" Bowl	• CP4199

See Visalighting.com/products/Olympia for more information

### SUGGESTED VARIATIONS

- Custom colors
- Integrate accents and trim from other product designs
- Larger diffuser sizes available

# **OLYMPIA** (cont.) CP4151, CP4155 and CP4159 Stem Suspension



FINISHES PB (Polished Brass) and BB (Brushed Brass) not available on CP4155 and CP4159

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)



#### Alternative Metal Finishes (Premium)



#### Metal Finish (Premium)

