# FAIRFAX™

# CP4211, CP4215 and CP4219 Stem Suspension




Visalighting.com/products/Fairfax

| Type: | Project: | Location: |
|-------|----------|-----------|
|       |          |           |







#### DIMENSIONS<sup>1,5</sup>

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(192) indicates an overall fixture height of 192"

#### ▲ OAH must be specified

DIA = Diameter OAH = Standard Overall Height X = Body Height NBS= Nominal Bowl Size

|     | CP4211             | CP4215             | CP4219             |
|-----|--------------------|--------------------|--------------------|
| W   | 26-1/2" (673 mm)   | 34-1/2" (876 mm)   | 41-1/2" (1054 mm)  |
| OAH | 25" (635 mm)       | 32" (813 mm)       | 38" (965 mm)       |
| Χ   | 7" (178 mm)        | 9"(229 mm)         | 10-1/2" (267 mm)   |
| NBS | 23x5" (584x127 mm) | 31x7" (787x178 mm) | 37x9" (787x229 mm) |




Structural Blocking Required (CP4219) (See Detail on Page 2)


#### **FEATURES**

- Uplight and bowl light separated for optical performance and wired for discreet operation
- · Integral power supply
- Modular design for replacement of LED source and driver
- Easy toolless bowl cleaning
- Mounts to standard electrical junction box (by others) with provided hardware for sloped ceiling up to 45 degrees from horizontal
- Spun metal trim
- Thermally formed 1/8" thick white acrylic diffuser with matte finish
  - UV stable
  - UL-94 HB Flame Class rated
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suited for exterior applications

### **RELATIVE SCALE DRAWING**



### **PHOTOMETRICS**









XPS

3 fedi Wallality

# FAIRFAX (cont.) CP4211, CP4215 and CP4219 Stem Suspension



#### Fill in shaded boxes using information listed below **MVOLT** MODEL1 SOURCE<sup>2</sup> **VOLTAGE FINISH** DIFFUSER OPTION<sup>3</sup> OPTION(S)4 OAH<sup>5</sup> CP4211 MVOLT • L30K • ABA $\mathsf{AF}$ See last page See page 1 DCC CP4215 L35K for finish XPS CP4219 L40K order codes See page 1

#### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 10%, Minimum 80CRI, within 3-step MacAdam

|        |       | CP4211              |                  |                     | CP4215           |                     |                  |                     | CP4219           |                     |                  |                     |                  |
|--------|-------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|
|        |       | Uplight             |                  | Downlight           |                  | Uplight             |                  | Downlight           |                  | Uplight             |                  | Downlight           |                  |
| SOURCE | ССТ   | Delivered<br>Lumens | Power<br>(Watts) |
| • L30K | 3000K | 8300                |                  | 2400                |                  | 12600               |                  | 4100                |                  | 21900               |                  | 6200                |                  |
| L35K   | 3500K | 8700                | 78               | 2500                | 39               | 13100               | 119              | 4300                | 53               | 22800               | 205              | 6500                | 67               |
| • L40K | 4000K | 8900                |                  | 2600                |                  | 13500               |                  | 4400                |                  | 23500               |                  | 6700                |                  |

## DIFFUSER OPTION<sup>3</sup>

Diffuser is matte white acrylic unless ABA option is selected

• ABA Hand Painted Alabaster Alternative



#### ABA

## OPTIONS<sup>4</sup> (Multiple selections allowed)

### ▲ Option availability may be interdependent with Other Options

| AF  | Add Finial. Addition of AF option increases H dimension (height) by 1-1/8"                    |  |  |  |
|-----|---|--|--|--|
| DCC | Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations) |  |  |  |
| XPS | Express 10 day shipping. Items marked with a bullet (•) are not available with XPS            |  |  |  |

## **VOLTAGE**

| MVOLT | 120-277V, 50/60 Hz |
|-------|--------------------|
|-------|--------------------|

# AF OPTION



#### STRUCTURAL BLOCKING DETAIL (CP4219)



# FAIRFAX (cont.) CP4211, CP4215 and CP4219 Stem Suspension



#### FAIRFAX PRODUCT FAMILY

| C                           | 19" Deep Bowl    | • CB3472 |
|-----------------------------|------------------|----------|
| Sconces                     | 21" Shallow Bowl | • CB3474 |
| Surface Mount               | 19" Deep Bowl    | • CM1081 |
| Ceiling Units               | 27" Shallow Bowl | • CM1083 |
|                             | 27" Bowl         | • CP4211 |
| Stem Suspension<br>Pendants | 35" Bowl         | • CP4215 |
| Tondants                    | 42" Bowl         | • CP4219 |
|                             | 27" Bowl         | • CP4271 |
| Rod Suspension<br>Pendants  | 35" Bowl         | • CP4275 |
| Citaditis                   | 42" Bowl         | • CP4279 |

See <u>Visalighting.com/products/Fairfax</u> for more information

### SUGGESTED VARIATIONS

- Custom colors
- Integrate accents and trim from other product designs
- Larger diffuser sizes available

# FAIRFAX (cont.) CP4211, CP4215 and CP4219 Stem Suspension



#### **FINISHES** PB (Polished Brass) and BB (Brushed Brass) not available on CP4215 and CP4219

Specify color code when ordering. For accurate color matching, individual paint and finish samples are available upon request. For more information about our finishes visit <u>visalighting.com/finishes</u>

#### Powder Coat Paint Finishes (Standard)



#### Alternative Metal Finishes (Premium)



#### Metal Finish (Premium)

