# FAIRFAX™


# CP4271, CP4275 and CP4279

**Rod Suspension** 



Visalighting.com/products/Fairfax

Type: Project: Location:





#### DIMENSIONS<sup>1,5</sup>

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(192) indicates an overall fixture height of 192"

#### ▲ OAH must be specified

W = Width OAH = Standard Overall Height X = Body Height NBS= Nominal Bowl Size MP = Stem Accent Midpoint

	CP4271	CP4275	CP4279
W	26-1/2" (673 mm)	34-1/2" (876 mm)	41-1/2" (1054 mm)
OAH	25" (635 mm)	32" (813 mm)	38" (965 mm)
Χ	7" (178 mm)	9"(229 mm)	10-1/2" (267 mm)
NBS	23x5" (584x127 mm)	31x7" (787x178 mm)	37x9" (787x229 mm)
MP	20" (508 mm)	27" (686 mm)	33" (838 mm)




Structural Blocking Required (CP4279) (See Detail on Page 2)


#### **FEATURES**

- Uplight and bowl light separated for optical performance and wired for discrete operation
- Integral driver
- Easy toolless bowl cleaning
- Mounts to standard electrical junction box (by others) with provided hardware for sloped ceiling up to 45 degrees from horizontal
- Spun metal trim
- Thermally formed 1/8" thick white acrylic diffuser with matte finish
  - UV stable
  - UL-94 HB Flame Class rated
- No VOC powder coat paints; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suited for exterior applications

#### **RELATIVE SCALE DRAWING**



#### **PHOTOMETRICS**









XPS

sted 5 Year Warranty

## FAIRFAX (cont.) CP4271, CP4275 and CP4279 Rod Suspension



#### Fill in shaded boxes using information listed below **MVOLT** MODEL1 SOURCE<sup>2</sup> OPTION(S)4 **VOLTAGE FINISH** DIFFUSER OPTION<sup>3</sup> OAH<sup>5</sup> CP4271 L30K MVOLT ABA $\mathsf{AF}$ See last page See page 1 CP4275 L35K DCC for finish CP4279 L40K XPS order codes See page 1

#### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 10%, Minimum 80CRI, within 3-step MacAdam

		CP4271			CP4275			CP4279					
		Uplight		Downlight		Uplight		Downlight		Uplight		Downlight	
SOURCE	ССТ	Delivered Lumens	Power (Watts)										
• L30K	3000K	8300		2400		12600		4100		21900		6200	
L35K	3500K	8700	78	2500	39	13100	119	4300	53	22800	205	6500	67
• L40K	4000K	8900		2600		13500		4400		23500		6700	

#### DIFFUSER OPTION3

Diffuser is matte white acrylic unless ABA option is selected

• ABA Hand Painted Alabaster Alternative



### ABA

#### OPTIONS<sup>4</sup> (Multiple selections allowed)

▲ Option availability may be interdependent with Other Options

AF	Add Finial. Addition of AF option increases H dimension (height) by 1-1/8"			
DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)			
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS			

#### **VOLTAGE**

<b>MVOLT</b> 120-277	V, 50/60 Hz

#### AF OPTION



#### STRUCTURAL BLOCKING DETAIL (CP4279)



## FAIRFAX (cont.) CP4271, CP4275 and CP4279 Rod Suspension



#### FAIRFAX PRODUCT FAMILY

C	19"Deep Bowl	• CB3472
Sconces	21" Shallow Bowl	• CB3474
Surface Mount	19"Deep Bowl	• CM1081
Ceiling Units	27" Shallow Bowl	• CM1083
	27" Bowl	• CP4211
Stem Suspension Pendants	35" Bowl	• CP4215
	42" Bowl	• CP4219
	27" Bowl	• CP4271
Rod Suspension Pendants	35" Bowl	• CP4275
· c.i.ddiito	42" Bowl	• CP4279

See <u>Visalighting.com/products/Fairfax</u> for more information

### SUGGESTED VARIATIONS

- Custom colors
- Integrate accents and trim from other product designs
- Larger diffuser sizes available

## FAIRFAX (cont.) CP4271, CP4275 and CP4279 **Rod Suspension**



#### **FINISHES** PB (Polished Brass) and BB (Brushed Brass) not available on CP4275, and CP4279

Specify color code when ordering. For accurate color matching, individual paint and finish samples are available upon request. For more information about our finishes visit <u>visalighting.com/finishes</u>

#### Powder Coat Paint Finishes (Standard)



#### Alternative Metal Finishes (Premium)



#### Metal Finish (Premium)

