PARALLEL[™] CP5582/CP5583/CP5584/CP5585/CP5586/CP5588 12" Wide Pendant – Cable Suspended



VisaLighting.com/products/Parallel

Type:

Project:

Location:



DIMENSIONS^{1,7}


Overall height must be specified

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(192) indicates an overall fixture height of 192" W = WidthOAH = Standard Overall Height X = Body Height WT = Weight

Х

	CP5582	CP5583	CP5584	CP5585	CP5586	CP5588					
W		12-5/8" (321 mm)									
OAH		192" (4877 mm)									
X with White LED source	25" (635 mm)	36" (914 mm)	47" (1194 mm)	58" (1473 mm)	69" (1753 mm)	91" (2311 mm)					
X with RGB source	21" (533 mm)	30" (762 mm)	45" (1143 mm)	63" (1600 mm)	69" (1753 mm)	93-1/8" (2365 mm)					
WT	16 lbs	25 lbs	34 lbs	45 lbs	52 lbs	64 lbs					

RELATIVE SCALE DRAWING



FEATURES

- Integral driver
- Color changing RGB is DMX-512 compatible (controls by others)
- See DMX detail on page 3
- Optional downlight, 0-10V dimmable (controls by others), with Narrow, Medium or Wide optical distribution options
- Power cord is white; cables are stainless steel
- Canopy/Cable/Cord can be shipped ahead to speed installation
- Matte white acrylic panels; optional Lumicor® acrylic panels
- No VOC powder coat paint finish
- ETL listed for damp locations (not suited for exterior applications)



XPS

CP5585, CP5586, CP5588 - STRUCTURAL BLOCKING REQUIRED



PARALLEL (cont.) CP5582/CP5583/CP5584/CP5585/CP5586/CP5588 12" Wide Pendant – Cable Suspended

		F	ill in shaded boxe	s using information list	ed below			
			MVOLT					
MODEL ¹ CP5582 CP5583 CP5584 CP5585 CP5586	BODYLIGHT² • L30K L35K • L40K • RGB	DOWNLIGHT³ (Optional) • L30K L35K • L40K	Voltage MVOLT	DOWNLIGHT ⁴ OPTICS MED NRW WIDE	FINISH See last page for finish order codes	DIFFUSER ⁵ • KA • OLIN • SL	OPTION 6 XPS XPS not available on CP5585,	OAH7 See page
CP5588 See page 1		Bottom has square aperture with glow when no downlight specified		Required with Downlight Option			CP5586, CP5588	

BODYLIGHT SOURCE² (Select One)

Dimmable 0-10V to 1%, Minimum 83CRI, within 3-step MacAdam

Source	ССТ	CP5582		CP5583		CP5584		CP5585		CP5586		CP5588									
		Delivered Lumens	Power/ Watts																		
• L30K	3000K	6100		10900		14000		18600		21800		29700									
L35K	3500K	0010	6100	000	6100	000	0100	0100	0100	000	49	10900	86	14000	110	18000	147	21800	172	29700	234
• L40K	4000K	6300		11200		14400		19200		22500		30500									
• RGB			24		40		56		79		87		119								


Bodylight and downlight are separately switched and controlled/dimmed

DOWNLIGHT SOURCE³


Bottom has square aperture with glow when no downlight specified									
		CP5582/C	P5583	CP5584/85	/86/88				
C	CCT								

Source	ССТ	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts	
• L30K	3000K	1800		2700		
L35K	3500K	1800	18	2800	28	
• L40K	4000K	1900		2800		

PHOTOMETRICS




Body Light



WIDE 84° Beam





MED 48° Beam

DOWNLIGHT OPTICS⁴ For downlight only MED 48° Beam NR\ WID

VOLTAGE

L80 (reported)

DIFFUSER OPTIONS⁵

MVOLT 120-277V, 50/60 Hz

W	34° Beam	
DE	84° Beam	B

BODYLIGHT LUMEN MAINTENANCE RATING

L80 (reported) >60,000 hrs

DOWNLIGHT LUMEN MAINTENANCE RATING

>55,000 hrs



BOTTOM WITH DOWNLIGHT

BOTTOM – NO DOWNLIGHT



Diffuser is matte white acrylic if no option is selected • KA Kauri Lumicor

• OLIN	Oyster Linen Lumicor
• SL	Silver Spun Lumicor






PARALLEL (cont.) CP5582/CP5583/CP5584/CP5585/CP5586/CP5588 12" Wide Pendant – Cable Suspended

OPTION⁶

XPSExpress 10 day shipping. Items marked with a bullet (•) are not available with XPS
XPS not available on CP5575, CP5576, CP5578





STRUCTURAL BLOCKING DETAIL



CP5585, CP5586, CP5588 – STRUCTURAL BLOCKING REQUIRED

PARALLEL PRODUCT FAMILY

Indoor Sconce		• CB5530
Indoor Pendants	4" Wide	• CP5562, CP5563, CP5564, CP5565, CP5566, CP5568
	8" Wide	• CP5572, CP5573, CP5574, CP5575, CP5576, CP5578
	12" Wide	• CP5582, CP5583, CP5584, CP5585, CP5586, CP5588

See Visalighting.com/Products/Parallel for more information

SUGGESTED VARIATIONS

- Custom colors
- Stem mount
- Custom graphics



PARALLEL (cont.) CP5582/CP5583/CP5584/CP5585/CP5586/CP5588 12" Wide Pendant – Cable Suspended



FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BJBG	Baja Beige	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue
DEOR	Deoro Gold	GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey
SBGN	Sagebrush Green	SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red

This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.