CP5640PSX SLEIGHT™

47"- Pendant - Low Voltage



Visalighting.com/products/Sleight

Type: Project: Location:






DIMENSIONS

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(60) indicates an overall fixture height of 60"

W = Width L = Length OAH = Maximum Overall Height X = Body Height


W 3-1/4" (83 mm) L 47" (1194 mm) OAH 60" (1524 mm) X 1-1/2" (38 mm)




FEATURES

- Use with PS24 Series of 24VDC Class II remote drivers. Each PS24 can power
 multiple fixtures and is available with 0-10V dimming. System costs are
 reduced by distributing the PS24 over multiple fixtures. Low-voltage class
 II wiring between the PS24 and connected fixtures simplifies installation.
 The PS24 is not included with the fixture; order separately see Accessories
 section on page 2
- Suspension cables carry low voltage power; one positive, one negative
- Fixture includes suspension cables to allow maximum overall height of 60". Cables are field adjustable for over heights less than 60"
- Frosted acrylic diffuser
- Antimicrobial finishes (no VOC) on all interior and exterior painted surfaces
- ETL listed for damp locations. Not suited for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS







CP5640PSX SLEIGHT (cont.)

47"- Pendant - Low Voltage



Fill in shaded boxes using information listed below CP5640PSX **24VDC** OPTION² MODEL SOURCE1 **VOLTAGE** FINISH CP5640PSX L30K(H) **24VDC** DCC See last page JBC L30K(L) for finish L35K(H) order codes L35K(L) L40K(H) L40K(L)

VOLTAGE

24VDC

24VDC

SOURCE¹ (Select one)

Dimmable 0-10V to 10%, Minimum 80CRI, within 3-step MacAdam

SOURCE	ССТ	Delivered Lumens	Power (Watts)
L30K(H)	3000K	3350	67
L30K(L)	3000K	1450	30
L35K(H)	3500K	3400	67
L35K(L)	3500K	1500	30
L40K(H)	4000K	3400	67
L40K(L)	4000K	1500	30

OPTIONS² (Multiple Selections Allowed)


A Option availability may be interdependent with Other Options

DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)			
JBC	Junction box cover (required for drywall installations)			

MOUNTING DETAIL

Ceiling Tile Installation (for PSX models)

Drywall Ceiling Installation (for PSX models) (Junction box cover is required - specify JBC option; finish matches fixture)



ACCESSORIES (Order Separately)

PS-24VDC90W01	24VDC 90 watt power supply; no dimming, specify 120V or 277V input. 75' maximum remote distance using AWG wire. Express 10 day shipping option (XPS) available.	
PS-24VDC90W02	24VDC 90 watt power supply; 0-10V dimmable, specify 120V or 277V input. 20' maximum remote distance. Express 10 day shipping option (XPS) available.	

CP5640PSX SLEIGHT (cont.)

47"- Pendant - Low Voltage



SLEIGHT PRODUCT FAMILY

Semi Recessed,	16"	• CV1970
Integral Driver	32"	• CV1972
Surface Mount,	16"	• CV1976PSX
Low Voltage	32"	• CV1980PSX
Dondonto	47"	• CP5640
Pendants		• CP5640PSX

See <u>Visalighting.com/products/Sleight</u> for more information

SUGGESTED VARIATIONS

- Custom color
- Ceiling to wall connection to continue up wall into ceiling
- Increase length (4" to 10" increments)

CP5640PSX SLEIGHT (cont.)

47" - Pendant - Low Voltage



FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)



Alternative Metal Finishes (Premium)



Metal Finish (Premium)

