# $WAND^{\mathsf{m}}$

## CV4185 and CV4186 Surface Mount – Remote Driver



Visalighting.com/products/Wand

Type: Project: Location:







#### DIMENSIONS<sup>1</sup>


Depth is measured from wall to front of fixture

W = Width H = Height D = Depth


	CV4185	CV4186	
W	23-1/2" (597 mm)	34-1/2" (876 mm)	
Н	2" (51 mm)		
D	2-3/4" (70 mm)		




- · Remote driver
- Versatile mounting; ceiling or wall mount (vertical or horizontal orientation)
- Surface Mount
- Ceiling installations for drywall only
- Diffuser is 1/8" thick extruded white acrylic with frosted finish
- No VOC powder coat paint finish; low VOC clear coat on metal finishes
- ETL listed for damp locations



### **RELATIVE SCALE DRAWING**



#### **PHOTOMETRICS**












S F

ted 5 Year Warranty





#### Fill in shaded boxes using information listed below **MVOLT** MODEL1 SOURCE<sup>2</sup> **VOLTAGE DIFFUSER RETAINER HOUSING FINISH** OPTION(S)3 CV4185 • L30K(H) $\mathsf{MVOLT}$ **FINISH** DCC See last page CV4186 • L30K(L) JBC See last page for finish MRI L35K(H) See page 1 for finish order codes XPS L35K(L) order codes • L40K(H) • L40K(L)

#### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

		CV4185		CV4186	
Source	ССТ	Delivered Lumens	Power (Watts)	Delivered Lumens	Power (Watts)
• L30K(H)	3000K	1100	14	1600	21
• L30K(L)	3000K	750	10	1100	13
L35K(H)	3500K	1100	14	1600	21
L35K(L)	3500K	750	10	1100	13
• L40K(H)	4000K	1100	14	1700	21
• L40K(L)	4000K	750	10	1100	13

#### **VOLTAGE**


MVOLT	120-277V, 50/60 Hz

#### OPTIONS<sup>3</sup> (Multiple Selections Allowed)

#### ▲ Option availability may be interdependent with Other Options

DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)
JBC	Junction box cover (5" square) for use with an existing 4" junction box. Painted to match surface housing finish
• MRI	MRI room application, not available with dimming
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with <b>XPS</b>

# MOUNTING DETAIL



# WAND (cont.) CV4185 and CV4186 Surface Mount – Remote Driver



#### WAND PRODUCT FAMILY

- CV4180 24" Semi-Recessed Integral Driver
- CV4181 35" Semi-Recessed Integral Driver
- CV4185 24" Surface Mount Remote Driver
- CV4186 35" Surface Mount Remote Driver

See Visalighting.com/products/Wand for more information

#### SUGGESTED VARIATIONS

- 2700K
- · Custom color
- · Nominal 4' height

#### **FINISHES**

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard) Powder coat finishes available for Diffuser Retainer or Housing



#### Alternative Metal Finishes (Premium) Metal finishes available for Diffuser Retainer



Metal Finish (Premium)



This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.