MERIDIAN SQUARE™

U.S. Patent Pending

CV5710PSX, CV5712PSX and CV5714PSX Sconces - Low Voltage




Visalighting.com/products/Meridian-Square

Type: Project: Location:








DIMENSIONS¹

Depth is measured from wall to front of fixture

W = Width D = Depth

	CV5710PSX	CV5712PSX	CV5714PSX
W	15" (381 mm)	28-1/8" (714 mm)	46-1/2" (1181 mm)
D	3-1/2" (89 mm)	4" (102 mm)	4" (102 mm)






VisaLighting.com


FEATURES

- · Remote driver
- High or low lumen output options
- Evenly illuminated diffuser
- Use with PS24 Series of 24VDC Class II remote power supplies. Each PS24 is available with 0-10V dimming. Low-voltage Class II wiring between the PS24 and connected fixtures simplifies installation. The PS24 is not included with fixtures; order separately- see Accessories on page 2
- Versatile mounting; ceiling or wall
- Surface mount
- Rolled extruded aluminum ring with vacuum formed frosted acrylic diffuser
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suitable for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS










АЛА СОПІРІ

MERIDIAN SQUARE (cont.)





Fill in shaded boxes using information listed below **24VDC** SOURCE² OPTION3 MODEL1 VOLTAGE **FINISH** CV5710PSX L30K(H) 24VDC DCC See last page CV5712PSX L30K(L) for finish CV5714PSX L35K(H) order codes L35K(L) See page 1 L40K(H) L40K(L)

Power Supply is not included - Order separately (See Accessory section below)


SOURCE² (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

		CV5710PSX		CV5712PSX		CV5714PSX	
SOURCE	ССТ	Delivered Lumens	Power (Watts)	Delivered Lumens	Power (Watts)	Delivered Lumens	Power (Watts)
L30K(H)	3000K	1800	20	3800	40	6800	69
L30K(L)	3000K	1400	16	2800	30	5100	53
L35K(H)	3500K	1800	20	3800	40	6800	69
L35K(L)	3500K	1400	16	2800	30	5100	53
L40K(H)	4000K	1800	20	3800	40	6800	69
L40K(L)	4000K	1400	16	2800	30	5100	53

VOLTAGE

MOUNTING DETAIL



OPTION3

▲ Option availability may be interdependent with Other Options

DCC Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)

ACCESSORY (Order separately)

	24VDC 90 watt power supply; 0-10V dimmable, specify 120V or 277V input. 20'
PS-24VDC90W02	maximum remote distance. Express 10 day shipping option (XPS) available. Can
	power maximum of (3) CV5700PSX fixtures using a single power supply

MERIDIAN SQUARE (cont.)

CV5710PSX, CV5712PSX and 5714PSX Sconces - Low Voltage



MERIDIAN SQUARE PRODUCT FAMILY

- CP5710 24" Pendant
- CP5712 36" Pendant
- CP5714 48" Pendant
- CV5710PSX 24" Sconce Low Voltage
- CV5712PSX 36" Sconce Low Voltage
- CV5714PSX 48" Sconce Low Voltage

See Visalighting.com/products/Meridian-Square for more information

SUGGESTED VARIATIONS

- Custom colors
- Pendant mount
- Surface mounted driver compartment

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)



Alternative Metal Finishes (Premium)



Metal Finish (Premium)



This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.