CB3942 SANIBEL™

Indoor Sconce



VisaLighting.com/products/Sanibel

Type: Project: Location:





DIMENSIONS1

Depth is measured from wall to front of fixture

W = Width H = Height D = Depth

	CB3942-14	CB3942-26							
W	14-3/4" (375 mm)	26-1/2" (673 mm)							
Н	2" (51 mm)								
D	2-7/8" (73mm)	3-1/4" (83 mm)							







FEATURES


- Die cast aluminum housing
- Frosted acrylic lens
- May be mounted in uplight or downlight orientation
- High and low lumen output options
- Standard 80+CRI Optional 90+ CRI
- Dimmable 0-10V to 1%
- · Remote driver standard and included
- Easily cleaned slim profile
- Non-VOC powder coat paint finish
- ETL listed for damp locations; not suitable for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS





Uplight

Downlight







CB3942 SANIBEL (cont.)

Indoor Sconce



Fill in shaded boxes using information listed below — MVOLT

MODEL¹
(B3942-14
(B3942-26
See page 1

SOURCE² L30K(H) L30K(L) L35K(H) L35K(L) L40K(H)

L40K(L)

SOURCE OPTION³ 90CRI

Minimum 80CRI is standard if option is not selected

VOLTAGE MVOLT MOUNTING OPTION⁴ NOJBC JBC2 JBC4

FINISH


See last page for finish order codes

SOURCE² (Select one source)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

		CB394	12-14	CB3942-26			
SOURCE	ССТ	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts		
L30K(H)	3000K	925	21	1715	35		
L30K(L) 3000K 450		8	850	12			
L35K(H) 3500		950	21	1750	35		
L35K(L) 3500K		475	8	875	12		
L40K(H)	L40K(H) 4000K 975		21	1800	35		
L40K(L)	L40K(L) 4000K 475		8	900	12		

VANITY ILLUMINANCE



- CB3944-26-L35K(H)-90CRI with LLF = 0.85 used for calculations.
- Illuminance (fc) values are on a vertical plane 18" from the wall.
- Mirror bottom edge is 6" above countertop and fixture bottom edge is 6" above mirror.
- 80/50/20 room reflectances used. Results may vary based on fixture placement, mirror size, and interior finishes.

SOURCE OPTION3

Minimum 80CRI within 3-step MacAdam is standard if option is not selected

90CRI	Color rendering index minimum 90, minimum R9 value of 50 (delivered lumens
	reduced by 15%)

MOUNTING OPTION⁴ (Select one)


NOJBC	Mounting plate used when not mounting over standard junction box
JBC2	Junction box cover for use with 2"x4" junction box (by others). Painted to match finish.
JBC4	Junction box cover (4-1/2" square) for use with 4" octagonal junction box (by others). Painted to match finish

VOLTAGE


LUMEN MAINTENANCE RATING

L85 (reported)	≥60,000 hrs

Reported Lifetime per IES TM-21




Optional junction box cover for 2x4 junction box



Optional Junction Box Cover for 4x4 Junction Box JBC Option

REMOTE DRIVER DETAILS



Maximum Recommended Remote Wiring Distance from Remote Driver to Fixture

Wire Size AWG	Maximum Remote Distance in Feet						
	CB3924-14	CB3942-26					
12GA	650	400					
14GA	400	250					
16GA	250	150					
18GA	150	75					

CB3942 SANIBEL (cont.)

Indoor Sconce



SANIBEL PRODUCT FAMILY

High Abuse/	14"	• CB3944-14
Behavioral Health	26"	• CB3944-26
Indoor – Non-	14"	• CB3942-14
Behavioral Health	26"	• CB3942-26
Out de au	14"	• 0W3942-14
Outdoor	26"	• 0W3942-26

See <u>Visalighting.com/products/Sanibel</u> for more information

SUGGESTED VARIATIONS

- Custom colors
- Tunable white
- RGB or RGBW

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BJBG	Baja Beige	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue
DEOR	Deoro Gold	GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR S	Shoreline Grey
SBGN	Sagebrush Green	SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red