CP3970 OMNIENCE™

26" Diameter - Aircraft Cable



Visalighting.com/products/0mnience

Type: Project: Location:






DIMENSIONS⁴

▲ OAH must be specified

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(24) indicates an overall fixture height of 24". MP is the distance (in inches) from the bottom of the fixture to the bottom of the Stem Accent Junction.

W = Width X = Body Height OAH = Standard Overall Height MP = Midpoint


W 26" (660 mm) OAH 24" (610 mm) X 6-3/4" (171 mm) MP 20-1/2" (521 gm)




FEATURES

- Integral driver
- · Modular design for replacement of LED source and driver
- Upper perforations provide a luminous glow to reduce ceiling contrast if UPLT option is selected
- Mounts through 4" octagonal 2-1/8" deep electrical junction box (by others) with provided hardware for ceiling slopes up to 45° from horizontal
- Rolled extruded aluminum housing
- 1/8" thick diffuser with matte finish
 - UV stable
- Optional specialty diffuser materials available, including Vara Kamin's Impressions of Light® images which are replicated from Vara Kamin's original works of art
- Optional 1/8" thick impact resistant polycarbonate clear lens cover
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suited for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS









XPS

u 3 feat Wallality

CP3970 OMNIENCE (cont.)

26" Diameter - Aircraft Cable



Fill in shaded boxes using information listed below CP3970 MVOLT OPTION(S)3 MODEL SOURCE1 **VOLTAGE** FINISH DIFFUSER2 OAH4 • L30K OPTION **UPLT** MVOLT See last page XPS See page 1 L35K IRP • L40K for finish • VKMD order codes • VKMM • VKPG VKSS

SOURCE¹ (Select one)

Dimmable 0-10V to 1%, Minimum 83CRI within 3-step MacAdam

Sources	ССТ	Delivered Lumens	Power (Watts)
• L30K	3000K	9300	110
L35K	3500K	9300	110
• L40K	4000K	9600	110

VOLTAGE

MVOLT	120-277V, 50/60 Hz
-------	--------------------

DIFFUSER OPTIONS²

Diffuser is matte white acrylic if no option is selected

IRP	Impact resistant polycarbonate lens	VKMD VKPG VKSS	
• VKMD	Vara Kamin's Moon Drops®		
• VKMM	Vara Kamin's Morning Melody®		
• VKPG	Vara Kamin's Priscilla's Garden®	Vara Kamin options have been color-corrected to 4000K CCT and are available only with L40K source.	
• VKSS	Vara Kamin's Summer of Sundays®		

OPTIONS³ (Multiple selections allowed)

Option availability may be interdependent with 0ther 0ptions

UPLT	Lensed aperture in housing produces 3.8% uplight	
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS	

CP3970 OMNIENCE (cont.)

26" Diameter - Aircraft Cable



OMNIENCE PRODUCT FAMILY

Aircraft Cable	26" Diameter	• CP3970
	34" Diameter	• CP3975
	48" Diameter	• CP3995
Stem	26" Diameter	• CP3980
	34" Diameter	• CP3985
	48" Diameter	• CP3990
Ceiling Mount	26" Diameter	• CM1830

See Visalighting.com/products/Omnience for more information

SUGGESTED VARIATIONS

- · Remote driver
- Custom colors

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

