CB1851 SOLE™


Illuminated Mirror for Behavioral Health/High Abuse Care



VisaLighting.com/products/Sole

Type: Project: Location:






DIMENSIONS

W = Width H = Height RD = Recessed Depth

W	20" (508 mm)						
Н	30" (762 mm)						
RD	3-5/8" (92 mm)						


See framing detail on page 3




FEATURES

- BAA (Buy American Act) and BABA (Build American, Buy America) compliant
- Remote driver box is delivered wired and attached to the back of the LED assembly
- Recommend removing driver box from LED assembly and mounting in a remote location to allow servicing without disturbing mirror installation
- Optional amber LED Night Light
- IP65 rated for wash down applications
- IK10+ (100 joules) Impact resistant polycarbonate mirror
- Ligature resistant
- Heavy duty 5/16" machined aluminum frame
- Tamper resistant hardware
- Optional antimicrobial coating (no VOC) on mirror frame
- Scratch resistant coating for polycarbonate mirror surface; abrasion resilient silicone hard coating offering the ultimate level of scratch resistance
- No VOC powder coat paint
- ETL listed for wet locations. Not suited for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS














Buy America Compliant

IP65

ADA Compliant ETL Listed

year warranty

CB1851 SOLE (cont.)





Fill in shaded boxes using information listed below CB1851 **MVOLT** MODEL SOURCE¹ SOURCE OPTION² OPTION3 **VOLTAGE** FINISH L30K(H) **MVOLT** NGT AMC See last page L30K(L) for finish L35K(H) order codes L35K(L) L40K(H) L40K(L)

SOURCE¹ (Select one)

Dimmable 0-10V to 1%

Minimum 90CRI, within 3-step MacAdam

Source	ССТ	Delivered Lumens	Power/Watts			
L30K(H)	3000K	675	20			
L30K(L)	3000K	325	9			
L35K(H)	3500K	675	20			
L35K(L)	3500K	325	9			
L40K(H)	4000K	675	20			
L40K(L)	4000K	325	9			

⁻L output intended to deliver 20fc maintained iluminance at 24 inches from center of mirror face. Intended for users between ages 25-65.

SOURCE OPTION²

		Delivered Lumens	Power/Watts
NGT	Night Light (amber LED) (non-dimming)	50	6

OPTION3

	·
AMC	Antimicrobial coating (no VOC) for painted surfaces

VOLTAGE

M	IVOLT	120-277V, 50/60 Hz
---	-------	--------------------

LUMEN MAINTENANCE RATING

,	
L80 (reported)	> 60,000 hrs


⁻H output intended to deliver 40fc maintained illuminance at 24 inches from center of mirror face. Intended for users over age 65.

CB1851 SOLE (cont.)


Illuminated Mirror for Behavioral Health/High Abuse Care



FRAMING DETAIL



REMOTE DRIVER INFORMATION



Maximum Recommended Remote Wiring Distance from remote driver box to fixture

- 18AWG 50ft
- 16AWG 80ft
- 14AWG 130ft
- 12AWG 200ft
- 10AWG 330ft

See Sole <u>field instructions</u> for 2" x 4" wood furring dimensions.

- · Cardboard hole template provided with each mirror
- No parts from Visa Lighting required prior to installation of wall board. 2" x 4" wood furring is
 installed after cutting the hole in the wall for the LED assembly
- 2" x 4" wood furring must be installed as described, to achieve rated impact resistance and to avoid a safety hazard
- Remote driver box is delivered wired and attached to the back of the LED assembly
- Recommend removing driver box from LED assembly and mounting in a remote location to allow servicing without disturbing mirror installation

SOLE PRODUCT FAMILY

- CB1851
- CB1853
- CB1855
- CB1857

See <u>Visalighting.com/products/</u>Sole for more information

CB1851 SOLE (cont.) Illuminated Mirror for Behavioral Health/High Abuse Care



FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are available upon request. For more information about our finishes visit visalighting.com/finishes.

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BJBG	Baja Beige	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue
DEOR	Deoro Gold	GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR Shoreline Grey	
SBGN	Sagebrush Green	SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red