

OW2482 PASSAGE™

Junction Box Mount with Integral Power Supply



[Visalighting.com/products/Passage](https://visalighting.com/products/Passage)


Type: _____ Project: _____ Location: _____



DIMENSIONS

Depth is measured from wall to front of fixture
 L = Length H = Height D = Depth

- L 37-1/4" (946 mm)
- H 2-1/2" (64 mm)
- D 2-3/4" (70 mm)




Use JBC option for 4x4 octagonal or rectilinear junction box


FEATURES

- High or low lumen output
- Luminous or Forward Throw output
- Modular design for replacement of LED source or driver
- Integral high power factor electronic power supply
- Optional dual circuit switching
- IP65 rated
- Bracket mounting system simplifies installation and maintenance
- Surface mount to horizontal 2x4 junction box. Optional junction box cover (JBC) available for 4x4 junction box
- Tamper resistant fasteners
- Polycarbonate diffuser
- No VOC powder coat paint finish; metal based sublimated wood look finish
- ETL Listed for wet location mounting 4' above grade


RELATIVE SCALE DRAWING



PHOTOMETRICS



LUM (Luminous Lens)



FT (Forward Throw Optic)



IP65



ADA Compliant



ETL Listed



5 Year Warranty

OW2482 PASSAGE (cont.)

Junction Box Mount with Integral Power Supply



Fill in shaded boxes using information listed below

OW2482		MVOLT			
MODEL	SOURCE¹ L30K(H) L30K(L) L35K(H) L35K(L) L40K(H) L40K(L)	VOLTAGE MVOLT	OPTIC² LUM FT	FINISH See last page for finish order codes	OPTION³ DS NOJBC JBC2 JBC4

SOURCE¹ (Select one)

Dimmable 0-10V to 1%, Minimum 82CRI, within 3-step MacAdam

Source	CCT	Delivered Forward Throw Lumens	Delivered Luminous Lumens	Power (Watts)
L30K(H)	3000K	2700	1900	40
L30K(L)	3000K	900	650	14
L35K(H)	3500K	2700	1900	40
L35K(L)	3500K	900	650	14
L40K(H)	4000K	2700	1900	40
L40K(L)	4000K	900	650	14

VOLTAGE

MVOLT	120-277V, 50/60 Hz
--------------	--------------------

OPTIC² (Select one)


LUM	Luminous Lens
FT	Forward Throw Optic

OPTION(S)³ (Multiple Selections Allowed)

⚠ Option availability may be interdependent with Other Options


DS	Dual circuit switching (includes 2 drivers). Lumen output and wattage is split in half for each circuit
JBC4	Adaptor plate and decorative cover for 4x4 octagonal or square junction box. Finish matches canopy and housing

PATH OF EGRESS - LUMINOUS LENS




OW2482 –H Downlight, Mounted at 10' AFF, .70 light loss factor used

PATH OF EGRESS - FORWARD THROW



JUNCTION BOX COVER (JBC4 option) MOUNTING DETAIL



OW2482 PASSAGE (cont.)

Junction Box Mount with Integral Power Supply



PASSAGE PRODUCT FAMILY

- OW2480 – 37” – Mullion Mount with Remote Power Supply
- OW2482 – 37” – Junction Box Mount with Integral Power Supply
- OW2484 – 72” – Mullion Mount with Remote Power Supply
- OW2486 – 72” – Junction Box Mount with Integral Power Supply

SUGGESTED VARIATIONS

- Custom colors

See [Visalighting.com/products/Passage](https://visalighting.com/products/Passage) for more information

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are [available upon request](#). For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)

						
AGGY Agate Grey	ALGN Alpine Green	BMAT Bronze Matte	BRNZ Bronze	BSIL Blade Silver	CVBL Cove Blue	DEOR Deoro Gold
						
GLWT Glacier White	GSIL Graphite Silver	HRGR Harbor Grey	JTBK Jet Black	OCBL Ocean Blue	SHGR Shoreline Grey	SBGN Sagebrush Green
						
SLGR Slate Grey	SSTP Sierra Taupe	TRCN Terracotta Canyon	TRWT Traffic White	VBLK Velvet Black	VNRD Vineyard Red	

