CP5321 AIR FOIL™

48" Body Height x 36" Width



VisaLighting.com/products/Air-Foil

Type: Project: Location:








DIMENSIONS⁶


▲ OAH must be specified

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(192) indicates an overall fixture height of 192"

W = Width D = Depth OAH = Standard Overall Height X = Body Height




RELATIVE SCALE DRAWING



FEATURES

- BAA (Buy American Act) and BABA (Build American, Buy America) compliant
- Integral driver
- Modular design for replacement of LED source and driver
- Optional LED downlight (controls by others)
- Edge lit trim
- Color changing RGB is DMX compatible (controls by others)
- Matte white acrylic diffuser
- Optional specialty diffuser materials available
- Power cord is white; cable is stainless steel
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not recommended for exterior applications

PHOTOMETRICS









Ceiling Height = 24' Silhouette Height = 6'

CP5321 AIR FOIL (cont.)

48" Body Height x 36" Width



Fill in shaded boxes using information listed below CP5321 **MVOLT** BODYLIGHT1 MODEL **DOWNLIGHT²** VOLTAGE DOWNLIGHT³ OPTION4 **TRIM FINISH CANOPY FINISH** OAH⁵ L30K **MVOLT** OPTICS (Optional) DCC L35K See last page See last page See page 1 L30K(H) (Optional) for finish for finish L40K L30K(L) MED order codes order codes RGB L35K(H) NRW L35K(L) WIDE L40K(H) Required L40K(L) with downlight

BODYLIGHT¹ (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

Source	сст	Delivered Lumens	Power (Watts)
L30K	3000K	10700	93
L35K	3500K		93
L40K	4000K	11000	93
RGB			107

DOWNLIGHT² (Optional)

option

Fixture bottom is solid if no downlight is specified

Source	ССТ	Delivered Lumens	Power (Watts)
L30K(H)	3000K	2900	28
L30K(L)	3000K	1400	14
L35K(H)	3500K	3000	28
L35K(L)	3500K	1500	14
L40K(H)	4000K	3100	28
L40K(L)	4000K	1500	14

DOWNLIGHT OPTICS³ (Optional)

Required with downlight option

MED	49° Beam
NRW	35° Beam
WIDE	70° Beam

VOLTAGE		
MVOLT	120-277V, 50/60 Hz	

DIFFUSER

Diffuser is matte white acrylic

OPTION4




Option availability may be interdependent with Other Options

DCC

Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)

STRUCTURAL BLOCKING DETAILS



CP5321 AIR FOIL (cont.) 48" Body Height x 36" Width



AIR FOIL PRODUCT FAMILY

Indoor Wall	51" with downlight option	• CB5301
Sconce	55"	• CB5303
Pendant	48" H x 16" W	• CP5301
	48" H x 24" W	• CP5311
	48" H x 36" W	• CP5321
	24" H x 16" W	• CP5393
	36" H x 16" W	• CP5395
Outdoor Wall Sconce	55"	• 0W5303

See <u>VisaLighting.com/families/Air-Foil</u> for more information

SUGGESTED VARIATIONS

- Tandem units
- Custom printed overlay on lenses
- Graphics (school/company logos)

CP5321 AIR FOIL (cont.) 48" Body Height x 36" Width



FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)



Alternative Metal Finishes (Premium)



Metal Finish (Premium)



BA Brushed Aluminum