CM1911-W UNITY™ SLOT

3" Single Recessed Ceiling Unit



VisaLighting.com/Families/Unity

Type: Project: Location:






DIMENSIONS

W = Weight L = Length D = Depth RD = Recessed Depth WT = Weight W (76 mm) 47" (1194 mm) Painted Flange D 4" (102 mm) (FLGD Option) 4" RD(102 mm) WT 8.8 lbs Diffuser


FEATURES

- Integral drivers
- Optional 90+ CRI
- Formed acrylic lenses
- Snap-in acrylic lens for toolless access
- Drywall and T-Grid mounting
- ETL listed for damp locations. Not suited for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS











CM1911-W UNITY SLOT (cont.)

3" Single Recessed Ceiling Unit



Fill in shaded boxes using information listed below CM1911-W SOURCE OPTION² **VOLTAGE³** DIMMING CONTROL⁴ MOUNTING⁵ MODEL SOURCE1 **FINISH** L30K(H) 90CRI 347V OPTION FLGD (select finish) (for FLGD option) MVOLT DALI L30K(L) SBAR Minimum 80CRI is See last page L35K(H) **TBAR** standard if option for finish L35K(L) is not selected order codes L40K(H) L40K(L)

SOURCE¹ (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

Source	CCT Range	Delivered Lumens	Power (Watts)		
L30K(H)	3000K	3900	42		
L30K(L)	3000K	1950	19		
L35K(H)	3500K	4000	42		
L35K(L)	3500K	2000	19		
L40K(H)	4000K	4100	42		
L40K(L)	4000K	2000	19		

SOURCE OPTION²

80 CRI within 3-step MacAdam is standard if option is not selected

90CRI	Color rendering index minimum 90, minimum R9 value of 50 (delivered
	lumens reduced by 5%)

DIMMING CONTROL OPTION 4

▲ Option availability may be interdependent with Voltage, Source or Other Options Unit is 0-10V dimmable to 1% if no dimming option is selected

ĺ	DALI	Control via DALI protocol, dimming to minimum 1% (not available with 347V)
ı	VALI	CONTROL VIA DALI PROTOCOL, UNTILINING TO MINIMINITUM 17% (MOL dydliddie Willi 54/V)

MOUNTING OPTION⁵ (Select one)

FLGD	Flanged drywall ceiling (Select finish color)					
SBAR	Screw-slot lay-in t-grid ceiling					
TBAR	9/16" and 15/16" standard lay-in t-grid ceiling					

VOLTAGE³ (Select one)

MVOLT	120-277V, 50/60 Hz					
347V	347V, 50/60 Hz					

CM1911-W UNITY SLOT (cont.)

3" Single Recessed Ceiling Unit



UNITY SLOT PRODUCT FAMILY

	• CB1911-T — 3" Tunable Slot Sconce						
Wall Units	• CB1911-W — 3" Slot Sconce						
	\bullet CM1910-W $-$ 3" Tandem Overbed Units						
Ceiling	• CM1910-T — 3" Tunable Tandem Overbed Units						
Mount Units	\bullet CM1911-W $-$ 3" Single Slot Ceiling Unit						
	• CM1911-T — 3" Tunable Slot Ceiling Unit						

See <u>Visalighting.com/families/Unity-Healthcare-Lighting</u> for more information

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue	DEOR	Deoro Gold
GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey	SBGN	Sagebrush Green
SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red		