

CP3990 OMNIENCE™

48" Diameter - Stem


[Visalighting.com/products/Omnience](https://visalighting.com/products/Omnience)

Type: _____ Project: _____ Location: _____



DIMENSIONS⁴


STRUCTURAL BLOCKING REQUIRED (DETAIL PAGE 2)

⚠ OAH must be specified


OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane.
Example - OAH(42) indicates an overall fixture height of 42".

W = Width X = Body Height OAH = Standard Overall Height

W 48" (1219 mm)
OAH 42" (1066 mm)
X 6-3/4" (171 mm)




RELATIVE SCALE DRAWING



FEATURES

- Integral driver
- Modular design for replacement of LED source and driver
- Upper perforations provide a luminous glow to reduce ceiling contrast if UPLT option is selected
- Mounts through 4" octagonal 2-1/8" deep electrical junction box (by others) with provided hardware for ceiling slopes up to 45° from horizontal
- Rolled extruded aluminum housing
- 1/8" thick diffuser with matte finish
 - UV stable
- Optional 1/8" thick impact resistant polycarbonate clear lens cover
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suitable for exterior applications

PHOTOMETRICS



CP3990 OMNIENCE (cont.)

48" Diameter - Stem



Fill in shaded boxes using information listed below

CP3990		-	MVOLT				
MODEL	SOURCE ¹		VOLTAGE MVOLT	FINISH	DIFFUSER ²	OPTION(S) ³	OAH ⁴
	<ul style="list-style-type: none"> L30K L35K L40K 			See last page for finish order codes	IRP	UPLT XPS	See page 1

SOURCE¹ (Select one)

Dimmable 0-10V to 1%, Minimum 83CRI within 3-step MacAdam

Sources	CCT	Delivered Lumens	Power (Watts)
• L30K	3000K	13400	157
L35K	3500K	13400	157
• L40K	4000K	13800	157

VOLTAGE

MVOLT	120-277V, 50/60 Hz
-------	--------------------

DIFFUSER OPTIONS²

Diffuser is matte white acrylic


IRP	Impact resistant polycarbonate lens
-----	-------------------------------------

OPTIONS³ (Multiple selections allowed)

⚠ Option availability may be interdependent with Other Options

UPLT	Lensed aperture in housing produces 3.8% uplight
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS

STRUCTURAL BLOCKING DETAIL



CP3990 OMNIENCE (cont.)

48" Diameter - Stem



OMNIENCE PRODUCT FAMILY

Aircraft Cable	26" Diameter	• CP3970
	34" Diameter	• CP3975
	48" Diameter	• CP3995
Stem	26" Diameter	• CP3980
	34" Diameter	• CP3985
	48" Diameter	• CP3990
Ceiling Mount	26" Diameter	• CM1830

SUGGESTED VARIATIONS

- Remote driver
- Custom colors

See [Visalighting.com/products/Omnience](https://visalighting.com/products/Omnience) for more information

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are [available upon request](#). For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)

AGGY Agate Grey	ALGN Alpine Green	BMAT Bronze Matte	BRNZ Bronze	BSIL Blade Silver	CVBL Cove Blue	DEOR Deoro Gold
GLWT Glacier White	GSIL Graphite Silver	HRGR Harbor Grey	JTBK Jet Black	OCBL Ocean Blue	SHGR Shoreline Grey	SBGN Sagebrush Green
SLGR Slate Grey	SSTP Sierra Taupe	TRCN Terracotta Canyon	TRWT Traffic White	VBLK Velvet Black	VNRD Vineyard Red	

