# $\begin{array}{l} \textbf{AVATAR}^{\mathsf{TM}} \, \mathsf{INDOOR} - \mathsf{SINGLE} \, \mathsf{ACCENT} \, \mathsf{BAR} \, \, (\mathsf{cont.}) \\ \mathsf{CV2009/CV2011/CV2013/CV2015} \end{array}$



VisaLighting.com/products/Avatar

Type: Project: Location:









#### DIMENSIONS1


Door Height = 7'
Ceiling Height = 9'
Silhouette Height = 6'

800-788-VISA

Depth is measured from wall to front of fixture

L = Length D = Depth W = Width


	CV2009	CV2011	CV2013	CV2015	
L	19-3/4" (502 mm)	25-1/8" (638 mm)	36-1/8" (918 mm)	47-1/4" (1200 mm)	
D	4" (102 mm)				
W	7-1/4" (184 mm)				



#### **FEATURES**

- BAA (Buy American Act) and BABA (Build American, Buy America) compliant
- Modular design for replacement of LED source and integral driver
- Vertical mounting; ceiling or wall mount (vertical or horizontal orientation)
- Mounts over standard electrical junction box (by others) with provided hardware
- Removable cam-action hinged frame for ease of maintenance
- Auxiliary mounting holes and hardware provided
- Extruded aluminum backplate and center accent; die-cast end caps.
   Solid metal accent
- High impact white acrylic diffuser
  - UV stable
  - UL-94 HB Flame Class rated
- No VOC powder coat paint
- ETL listed for damp locations. Not suited for exterior applications

### **PHOTOMETRICS**













# AVATAR INDOOR – SINGLE ACCENT BAR (cont.) CV2009/CV2011/CV2013/CV2015



#### Fill in shaded boxes using information listed below **MVOLT** MODEL<sup>1</sup> VOLTAGE SOURCE<sup>2</sup> **FINISH** OPTION(S)3 CV2009 • L30K(H) MVOLT DCC CV2011 • L30K(L) See last page PMO (Painted) for finish CV2013 PMO (BA) L35K(H) order codes CV2015 L35K(L) XPS • L40K(H) See page 1 • L40K(L)

#### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

		CV2009		CV2011		CV2013		CV2015	
Source	ССТ	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts
• L30K(H)	3000K	1200	15	1600	19	2400	29	3300	38
• L30K(L)	3000K	800	9	1100	13	1600	19	2200	25
L35K(H)	3500K	1200	15	1600	19	2400	29	3300	38
L35K(L)	3500K	800	9	1100	13	1600	19	2200	25
• L40K(H)	4000K	1200	15	1700	19	2500	29	3400	38
• L40K(L)	4000K	800	9	1100	13	1700	19	2200	25

### **VOLTAGE**

**MVOLT** 120-277V, 50/60 Hz

### OPTIONS<sup>3</sup> (Multiple Selections Allowed)

▲ Option availability may be interdependent with Other Options

DCC	Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)
PMO (Painted)	Perforated metal overlay painted. Color Code Required - see finish order codes on last page
PMO (BA)	Perforated metal overlay in Brushed Aluminum
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS

## AVATAR INDOOR – SINGLE ACCENT BAR (cont.) CV2009/CV2011/CV2013/CV2015



#### **AVATAR PRODUCT FAMILY**

	Single Bar	• 0W1301, 0W1303, 0W1305, 0W1307		
Outdoor	Dual Bars	• 0W1311, 0W1313, 0W1315, 0W1317		
	Perforated	• 0W1331, 0W1333, 0W1335, 0W1337		
lu de eu	Single Bar	• CV2009, CV2011, CV2013, CV2015		
Indoor	Dual Bars	• CV2025, CV2027, CV2029, CV2031		

SUGGESTED VARIATIONS

- Increase length
- Add/remove bar stock

See <u>Visalighting.com/Products/Avatar</u> for more information

#### **FINISHES**

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)



Metal Finish (Premium)

- Premium metals for PMO(BA) option only



**BA** Brushed Aluminum

This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.