

OP2252/OP2253/OP2254 SEQUENCE™

8" Diameter Outdoor Pendants – Cord and Cable Suspension


VisaLighting.com/products/Sequence

Type: _____ Project: _____ Location: _____



DIMENSIONS⁴

OAH MUST BE SPECIFIED

DIA = Diameter X = Body Height OAH = Overall Height



OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(48) indicates an overall fixture height of 48"

	OP2252	OP2253	OP2254
X	25" (635 mm)	36" (914 mm)	47" (1194 mm)
X w/ BTH option	Add 1/2" to X		
DIA	8" (203 mm)		
OAH	48" (1219 mm)	60" (1524 mm)	72" (1829 mm)


FEATURES

- High or low lumen output
- Integral driver
- RGB is DMX controlled with RDM for digital addressing
- IP65 rated
- Parallel mounting cables reduce twisting
- Mounts to standard electrical junction box (by others)
- **Tether cables connecting fixtures to each other are considered structural and are to be designed by a qualified structural engineer**
- Tether cable connections to the fixture accept 3/32" to 1/4" diameter cables
- Crossing secondary cables at the bottom Tether are limited to 1/8" when the primary cable is 1/4"
- Black power cord
- Fixture body tested to ANSI C136.31 'American National Standard for Roadway and Area Lighting Equipment' at or above 3G vibration levels for 100,000 cycles in X, Y, Z axes
- Matte white acrylic diffuser
- No VOC powder coat finish on end caps and mounting component
- ETL listed for wet locations

RELATIVE SCALE DRAWING



PHOTOMETRICS



OP2252/OP2253/OP2254 SEQUENCE (cont.)

8" Diameter Outdoor Pendants – Cord and Cable Suspension



Fill in shaded boxes using information listed below

OP2252		-		MVOLT							
MODEL¹		SOURCE²		VOLTAGE		FINISH		MOUNTING OPTION³		OA⁴	
OP2252		L30K(H)		MVOLT				BTH			
OP2253		L30K(L)				See last page for finish order codes				See page 1	
OP2254		L35K(H)									
		L35K(L)									
		L40K(H)									
		L40K(L)									
		RGB									

See page 1

SOURCE² (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

Source	CCT	OP2252		OP2253		OP2254	
		Delivered Lumens	Power/Watts	Delivered Lumens	Power/Watts	Delivered Lumens	Power/Watts
L30K(H)	3000K	4300	48	7600	86	9800	110
L30K(L)	3000K	2800	35	5100	56	6500	72
L35K(H)	3500K	4300	48	7600	86	9800	110
L35K(L)	3500K	2800	35	5100	56	6500	72
L40K(H)	4000K	4400	48	7800	86	10100	110
L40K(L)	4000K	2900	35	5200	56	6700	72
RGB			29		43		57

VOLTAGE

MVOLT	120-277V, 50/60 Hz
-------	--------------------

LUMEN MAINTENANCE RATING

L80 (reported)	>60,000 hrs
----------------	-------------

MOUNTING OPTION³

No tether bottom is included if no option is selected

BTH	Bottom tether attachment (Tether option is recommended for high wind. A tether cable is to restrict movement of the light fixture and not provide structural support. See Catenary Design Guide for important information and warnings)
-----	---

TETHER ACCESSORIES (Order Separately)

Stainless Steel
Compression Sleeve
(AY-CS3/32)




Qty (10)

3/32" Stainless Steel Cable
(AY-CBL3/32-50)



50 feet

Tether Example



Accessory	Quantity

Accessories available for Visa Lighting's Outdoor Pendant (OP) applications.

If sourced elsewhere, materials must be of equivalent grade.

For technical specifications and installation information, see "[Installation Instructions](#)"

OP2252/OP2253/OP2254 SEQUENCE (cont.)

8" Diameter Outdoor Pendants – Cord and Cable Suspension



SEQUENCE OUTDOOR PENDANT PRODUCT FAMILY

Catenary	4" Diameter	• OP2232 , OP2233 , OP2234
	8" Diameter	• OP2262 , OP2263 , OP2264
Cord and Cable	4" Diameter	• OP2222 , OP2223 , OP2224
	8" Diameter	• OP2252 , OP2253 , OP2254
Stem	4" Diameter	• OP2242 , OP2243 , OP2244
	8" Diameter	• OP2272 , OP2273 , OP2274

SUGGESTED VARIATIONS

- Remote driver
- Custom colors

See [Visalighting.com/Products/Sequence](https://visalighting.com/Products/Sequence) for more information

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are [available upon request](#).

For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)

AGGY Agate Grey	ALGN Alpine Green	BMAT Bronze Matte	BRNZ Bronze	BSIL Blade Silver	CVBL Cove Blue	DEOR Deoro Gold
GLWT Glacier White	GSIL Graphite Silver	HRGR Harbor Grey	JTBK Jet Black	OCBL Ocean Blue	SHGR Shoreline Grey	SBGN Sagebrush Green
SLGR Slate Grey	SSTP Sierra Taupe	TRCN Terracotta Canyon	TRWT Traffic White	VLBK Velvet Black	VNRD Vineyard Red	

