## **AVATAR**<sup>™</sup> OUTDOOR – PERFORATED ACCENT OW1331/OW1333/OW1335/OW1337





VisaLighting.com/products/Avatar

Type: Project: Location:











#### DIMENSIONS1

Depth is measured from wall to front of fixture

L = Length D = Depth W = Width

	0W1331 0W1333		OW1335	0W1337	
L	19-3/4" (502 mm) 25-1/8" (638 mm)		36-1/8" (918 mm)	47-1/4" (1200 mm)	
D	4" (102 mm)				
W	7-1/4" (184 mm)				






Silhouette Height = 6'

#### **FEATURES**

- BAA (Buy American Act) and BABA (Build American, Buy America) compliant
- · Modular design for replacement of LED source and integral driver
- Vertical mounting standard (horizontal mounting optional)
- Mounts to standard electrical junction box (by others) and wall with provided hardware
- Removable cam-action hinged frame for ease of maintenance
- Extruded aluminum backplate and center accent, die-cast end caps.
  Solid metal or die-cast accent
- Sealed and gasketed construction
- High impact white acrylic diffuser
  - F1 rated, UV stable
  - UL-94 HB Flame Class rated
- No VOC powder coat paint or stainless steel finish
- ETL listed for wet location mounting 4' above grade

#### **PHOTOMETRICS**













800-788-VISA VisaLighting.com Page 1

Frame and

and End Cap

# **AVATAR** OUTDOOR – PERFORATED ACCENT (cont.) OW1331/OW1333/OW1335/OW1337



#### Fill in shaded boxes using information listed below **MVOLT** MODEL1 SOURCE<sup>2</sup> **VOLTAGE** FRAME/PERFORATION **ACCENT BAR AND** OPTION(S)3 OW1331 **END CAP FINISH** • L30K(H) MVOLT FINISH HMOW1333 • L30K(L) XPS See last page See last page OW1335 L35K(H) for finish for finish See page 1 OW1337 L35K(L) order codes order codes • L40K(H) See page 1 • L40K(L)

#### SOURCE<sup>2</sup> (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

	ССТ	OW1331		OW1333		OW1335		OW1337	
Source		Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/ Watts
• L30K(H)	3000K	1200	15	1600	19	2400	29	3300	38
• L30K(L)	3000K	800	9	1100	13	1600	19	2200	25
L35K(H)	3500K	1200	15	1600	19	2400	29	3300	38
L35K(L)	3500K	800	9	1100	13	1600	19	2200	25
• L40K(H)	4000K	1200	15	1700	19	2500	29	3400	38
• L40K(L)	4000K	800	9	1100	13	1700	19	2200	25

#### **VOLTAGE**

MVOLT	120-277V, 50/60 Hz

LUMEN MAINTENANCE RATING		
L90 (reported)	≥50,400 hrs	

### OPTIONS<sup>3</sup> (Multiple Selections Allowed)

▲ Option availability may be interdependent with Other Options

НМ	Horizontal mount (vertical is standard)	
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS	

### **AVATAR** OUTDOOR – PERFORATED ACCENT (cont.) OW1331/OW1333/OW1335/OW1337



#### **AVATAR PRODUCT FAMILY**

	Single Bar	• 0W1301, 0W1303, 0W1305, 0W1307		
Outdoor	Dual Bars	• 0W1311, 0W1313, 0W1315, 0W1317		
	Perforated	• 0W1331, 0W1333, 0W1335, 0W1337		
la de es	Single Bar	• CV2009, CV2011, CV2013, CV2015		
Indoor	Dual Bars	• CV2025, CV2027, CV2029, CV2031		

See <u>Visalighting.com/Products/Avatar</u> for more information

#### SUGGESTED VARIATIONS

- Increase length
- · Add/remove bar stock

#### **FINISHES**

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)



- Premium metals for Accent Bar and End Caps only

#### Metal Finishes (Premium)



This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.