# CP4408 HELLEN

16" Direct Pendant



VisaLighting.com/products/Hellen

Type: Project: Location:








#### DIMENSIONS<sup>4</sup>


DIA = Diameter X = Body Height OAH = Standard Overall Height WT = Weight



#### **FEATURES**

- Flat white acrylic lens and contoured bottom reflector
- High or low lumen output options
- Integral driver in canopy
- Optional 90+ CRI (2700K sources are 90+ CRI standard)
- Slim white power cord and aircraft cable suspension
- · Canopy is painted white
- Mounts over standard 4x4 or octagonal j-box
- Hand spun aluminum dome and bottom reflector
- Non-VOC powder-coat or environmentally friendly low VOC metal alternative finishes available on outer dome
- Non-VOC powder-coat finishes available on bottom reflector
- ETL listed for damp locations. Not suitable for exterior applications

#### **RELATIVE SCALE DRAWING**



#### **PHOTOMETRICS**







# CP4408 HELLEN (cont.)

#### 16" Direct Pendant



#### Fill in shaded boxes using information listed below **CP4408** MVOLT MODEL SOURCE1 SOURCE OPTION<sup>2</sup> **VOLTAGE OUTER FINISH** REFLECTOR FINISH OPTION3 OAH4 L27K(H) 90CRI MVOLT DCC See last page See last page See page 1 L27K(L) for finish for finish L30K(H) Minimum 80CRI is order codes order codes L30K(L) standard if option L35K(H) is not selected Canopy is painted white L35K(L) Minimum 90CRI L40K(H) Alternative and premium finishes is standard with L40K(L) are for outer dome only 2700K Sources

#### SOURCE<sup>1</sup> (Select one)

Dimmable 0-10V to 1%, Minimum 80CRI, within 3-step MacAdam

Source	CCT Range	Delivered Lumens**	Power (Watts)
L27K(H)*	2700K	2500	27
L27K(L)*	2700K	1700	17
L30K(H)	3000K	2600	27
L30K(L)	3000K	1800	17
L35K(H)	3500K	2700	27
L35K(L)	3500K	1850	17
L40K(H)	4000K	2800	27
L40K(L)	4000K	1900	17

<sup>\*\*</sup>Delivered lumen output tested with white interior finish

Dark interior finish reduces lumen output up to 10%

\*L27K sources are 90CRI standard

#### VOLTAGE

**MVOLT** 120-277V, 50/60 Hz

#### **LUMEN MAINTENANCE RATING**

**L70 (reported)** 50,000 hrs

#### SOURCE OPTION<sup>2</sup>

Minimum 80CRI within 3-step MacAdam is standard if option is not selected

90CRI	Color rendering index minimum 90. minimum R9 value of 50 (delivered lumens reduced by 6%):	
	option available for L30K, L35K, and L40K sources (L27K sources: 90CRI is standard)	

#### **OPTION**

A Option availability may be interdependent with Other Options

Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)

# CP4408 HELLEN (cont.)

### 16" Direct Pendant



















#### SUGGESTED VARIATIONS

- Stem suspension
- Remote driver
- Custom colors
- Larger size

#### See <u>Visalighting.com/products/Hellen</u> for more information

#### HELLEN PRODUCT FAMILY

- CP4408 16"
- CP4410 24"
- CP4412 32"

# CP4408 HELLEN (cont.)

#### 16" Direct Pendant



#### **FINISHES**

Specify color code when ordering. For accurate color matching, individual paint and finish samples are available upon request. For more information about our finishes visit visalighting.com/finishes

Powder Coat Paint Finishes (Standard)



Alternative Metal Finishes (Premium) Alternative finishes and premium metal finishes are for outer dome only



Metal Finish (Premium)

